



CAPRANO TD 15W-40



Multigrade oil for 4-stroke marine diesels.

APPLICATIONS

Propulsion engines
Transmission systems

- Specially recommended for lubricating supercharged marine propulsion engines (fishing, carriage of passengers or goods and Leisure).
- Also suitable for auxiliary units, for small gasoline engines and for transmission systems.

PERFORMANCE

Classifications
Manufacturers approvals
Suitable for engines

ACEA : E2
API : CG-4 / SH

Engines
BAUDOUIN : SMB 4
MAN : 271
MTU : TYPE 1
VOLVO : VDS

Reduction drives / reversing gear
ZF : TE ML 04C

MITSUBISHI (medium speed), PERKINS, IVECO, PETER, YANMAR...

CLIENT ADVANTAGES

Ensures long engine life

- Easier cold starts.
- High detergent and dispersant capability, guaranteeing internal engine cleanliness in all operating conditions.
- Excellent resistance to oxidation and good thermal stability.
- Good wear control for long engine and transmission system life.

CHARACTERISTICS

CAPRANO TD	Units	15W-40
Viscosity at 40°C	mm ² /s	105
Viscosity at 100°C	mm ² /s	14.4
TBN	mg KOH/g	10

The values given in this table are typical characteristic values given for illustrative purposes.

TOTAL LUBRIFIANTS
562 avenue du Parc de l'île
92029 NANTERRE
France

CAPRANO TD 15W-40
Sheet updated : 01/2012



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazard. A safety data sheet complying with current EC legislation can be obtained from your local sales representative.